Giving Shape to Ideas





bizhub 958

With 95 ppm print/copy output in high-resolution B&W, standard dual scanning at up to 240 opm, multiple finishing options and enhanced touch-and-swipe interface, the bizhub 958 brings maximum productivity to high-volume document demands and in-house, on-demand printing applications.

System Overview

-,		
System memory	4 GB	
System hard disk	250 GB	
Interface	10BASE-T/100BASE-TX/1000BASE-T Ethernet, USB 2.0,	
	Wi-Fi 802.11 b/g (opt.)	
Network protocols	TCP/IP (IPv4/IPv6), NetBEUI, SMB, LPD, IPP, SNMP, HTTP	
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP	
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35–210 gsm	
document feeder		
Printable paper size	Scanning/Copying: up to 11" x 17"	
	Printing: up to 11" x 17" full bleed on 12" x 18" paper	
	Custom paper sizes	
	Banner paper max.: 11.75" x 47.25"	
Printable	52–300 gsm	
paper weight		
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets	
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm	
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm	
Tray 3	1,500 sheets / 8.5" x 11" / 52-256 gsm	
Tray 4	1,000 sheets / 8.5" x 11" / 52-256 gsm	
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm	
LU-303 (optional)		
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm	
LU-205 (optional)		
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes /	
	52–300 gsm	
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm	
Finishing modes	Offset, group, sort, staple, punch, post-insertion,	
	z-fold, half-fold, tri-fold, booklet	
Output capacity	Max. with finisher: 3,200 sheets	
. It / .t I	Max. without finisher: 250 sheets	
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets	
Stapling output	(up to 209 gsm) Max.: 1,000 sheets	
	Mdx.: 1,000 sneets	
capacity Tri-fold	Unita 2 abasta	
Tri-fold capacity	Up to 3 sheets Max.: 30 sheets (tray), unlimited	
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet	
Rookiet	(up to 209 gsm)	
Booklet output	Max.: 100 sheets (tray), unlimited	
capacity	Mdx 100 Sheets (tray), unininited	
Copy/print volume	Max.: 300,000 pages/month ¹	
Copy/print volume Toner lifetime		
Imaging unit lifetime	Black: 40,800 pages	
Power consumption	400,000 pages / 1,200,000 pages (Developer) 208 V / 60 Hz, less than 3.8 kW (system)	
System dimensions	26.4" x 32.3" x 48.5" (W x D x H)	
System weight	Approx. 441 lb	

Printer Specifications

i initei specincati	i ilitei specilications	
Print resolution	1800 x 600 dpi, 1200 x 1200 dpi	
PDL	PCL 6 (XL 3.0), PCL 5c, PostScript 3 (ver. 3016), XPS	
Operating systems	Windows (x32/x64): Vista / 7 / 8	
	Windows Server: 2008 ³ / 2008 R2 / 2012 / 2012 R2	
	Macintosh OS X 10.6 / 10.7 / 10.8 / 10.9 / 10.10	
	UNIX / Linux / Citrix	
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation	
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF (v.17), encrypted	
	PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia	
	and mixplex, "Easy Set" job programming, overlay,	
	watermark, copy protection, carbon copy print	

Copier Specifications

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD ^E Polymerized Toner
Print speed	Up to 95 ppm (Portrait)
(8.5" x 11")	
Autoduplex speed	Up to 95 ppm (Portrait)
(8.5" x 11")	
1st copy out time	3.2 sec.
Warm-up time	Approx. 55 sec. ²
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25–400% in 0.1% steps, auto zooming
Copy functions	Chapter, cover and page insertion, proof copy (print
	and screen), adjustment test print, digital art functions,
	job setting memory, poster mode, image repeat,
	overlay, stamping, copy protection

Scanner Specifications

Scan speed	B&W / Colour: up to 240 opm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box,
	Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network
	TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact
	PDF, encrypted PDF, searchable PDF (optional), XPS,
	compact XPS, PPTX, searchable PPTX (optional),
	searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job
	programs, real time scan preview

Fax Specifications

Fax	Super G3 (optional)	
Transmission	Analog, i-Fax, Colour i-Fax, IP-fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box,	
	receipt to email/FTP/SMB, up to 400 job programs	

User Box Specifications

osei box specifications	
Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling
User box functionality	Reprint, combination, download, sending
	(email/FTP/SMB and fax), copy box-to-box

System Features

.)
nner)
ntl

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

Components and Options

Components and opt		
AU-102 Biometric	Finger vein scanner	
authentication		
AU-205H Universal	Various ID card technologies	
ID card reader		
EK-610 USB I/F kit	USB keyboard connection	
EK-611 USB I/F kit	USB keyboard connection, Bluetooth	
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 and 4 support	
FK-516 Fax board	Super G3 fax, digital fax functionality	
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output	
FS-536SD	50-sheet staple finisher, 20-sheet booklet finisher,	
Booklet finisher	2,200 sheets max. output	
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output	
FS-537SD	100-sheet stapling, 20-sheet booklet finisher,	
Booklet finisher	2,500 sheets max. output	
HD-524 Hard	Back-up HDD	
disk mirroring		
JS-602 Job	Separation for fax output, etc.	
separator for FS-537	- The state of the	
Keyboard	External keyboard (requires KH-102)	
KH-102	To place USB keyboard	
Keyboard holder	to place 03b keyboard	
	For use instead of touchestron	
KP-101 10-Key pad	For use instead of touchscreen	
LK-102 v3	PDF/A, PDF encryption, digital signature	
PDF enhancements		
LK-104 v3	Provides voice guidance functions	
Voice guidance		
LK-105 v3	Searchable PDF	
OCR text recognition		
LK-106	Supports native barcode printing	
Barcode fonts		
LK-107	Supports native Unicode printing	
Unicode fonts		
LK-108	Supports native OCR A and B font printing	
OCR A and B fonts		
LK-110 Enhanced	Generates various file formats incl. DOCX, XLSX	
image support	and combines LK-102 (encrypted PDF) + LK-105	
3	(searchable PDF/OCR functionality)	
LK-111	Print data compression for reduced network impact	
ThinPrint® Client	Time data compression for reduced nethoric impact	
LU-205	8.5" x 11" to 12" x 18", 2,500 sheets, 52–256 gsm	
Large capacity tray	0.5 X 11 to 12 X 10 , 2,500 sheets, 52 250 gsm	
LU-303	8.5" x 11", 3,000 sheets, 52–256 gsm	
Large capacity tray	0.5 X 11 , 5,000 sheets, 52 250 gsiii	
MK-735 Mount kit	Installation kit for ID card reader	
MK-742 Mount kit	Installation kit for FK-515 fax board	
OT-508 Output tray	Output tray used instead of finisher	
PI-507 Post-inserter		
for FS-537	Cover insertion, post finishing	
PK-520 Punch kit	2/2 h-l	
	2/3-hole punching, autoswitching	
for FS-536	2/21 1 1: 1: 1: 1: 1:	
PK-523 Punch kit	2/3-hole punching, autoswitching	
for FS-537	D : 16 H FO FOT/FO FOTOD	
RU-515 Relay unit	Required for the FS-537/FS-537SD	
	and FS-536/FS-536SD	
SC-508 Security kit	Copy Guard function (2x required)	
UK-212	Wireless LAN to network connector	
UK-501 Multi-feed	Detects multi-feeding in the document feeder	
detection kit		
WT-506 Working table	Authentication device placement	
WT-513 Working table	Used to mount the control panel in an upright position	
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching	
for FS-537		

 $^{^{\}rm 2}\,\mbox{Warm-up}$ time may vary depending on the operating environment and usage.

³ Certification pending.



Partnership.

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in:

IT Services

Information Management Enterprise Content Management (ECM) Document Management Automated Workflow Solutions Business Process Automation Security and Compliance Mobility

Application Services	Office Multifunction Business Solutions
Cloud Services	Commercial and Production Printers
IT Security	3D Printers
	Wide-Format Printers
	Laptops, Desktops and Computer Hardware
	Servers and Networking Equipment

Managed Print Services (MPS)

Managed Enterprise Services

Technology

© 2016 KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, bizhub and Giving Shape to Ideas are registered trademarks or trademarks of KONICA MINOLTA, INC. Trademarks of the Canadian Breast Cancer Foundation, used under licence. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design and specifications are subject to change without notice.





KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 5875 Explorer Drive, Suite 100, Mississauga, Ontario L4W 0E1





