



Up to 25 ppm print/copy output to keep pace with rising demands
 Optional dual scanning at up to 160 originals per minute
 Large 9" colour display with quick tablet-like touchscreen interface
 3rd-party software integration with standard web browser
 Built-in Emperon® print system, universal printer drivers
 Simitri® HD polymerized toner for high-resolution imaging
 Standard 250 GB HDD for on-board document storage
 Meets ISO 15408 and IEEE 2600.1 security standards
 Power-saving design with quick recovery from sleep mode
 6,650-sheet maximum capacity, tab printing support, carbon-copy printing
 Advanced authentication, secure print release, remote firmware updates
 Multiple bypass tray and detachable paper feed trays improve paper handling
 Finishing options for 80-page booklet-making
 50-sheet stapling, 2/3-hole punch, tri-fold, and more
 Downloadable apps to help you work faster and smarter
 i-Options to add functions for working more efficiently
 EPEAT Gold-certified, low power consumption to cut costs
 Mobile printing support (AirPrint, Google Cloud Print, NFC)

bizhub C258

COLOUR MID-VOLUME MULTIFUNCTION PRINTER

mfp



mfp



bizhub C258

COLOUR MID-VOLUME MULTIFUNCTION PRINTER

bizhub C258

Ideal for growing businesses, the bizhub C258 is a powerful, affordable colour MFP with superior Simitri HD image quality and fast 25 ppm print/copy output. Optional dual scanning at up to 160 opm brings information into your workflow faster – and enhanced touchscreen simplicity never slows you down.

System Overview

System memory	4 GB (when UK-211 is installed)
System hard disk	250 GB standard
Interface	10BASE-T/100BASE-TX/1000BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder (optional)	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm Reversing automatic document feeder or dual scan document feeder available
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray PC-410 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, staple, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 80,000 pages/month ¹
Toner lifetime	Black: 28,000 pages / CMY: 26,000 pages
Imaging unit lifetime	Black: 120,000 pages / 600,000 pages (Drum / Developer) CMY: 75,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 31" (W x D x H)
System weight	Approx. 187.39 lb

Copier Specifications

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	B&W / Colour: up to 25 ppm (Portrait)
Print speed (11" x 17")	B&W / Colour: up to 15 ppm (Portrait)
Autoduplex speed (8.5" x 11")	B&W / Colour: up to 25 ppm (Portrait)
1st copy out time	B&W: 6.1 sec. / Colour: 7.5 sec.
Warm-up time	Approx. 20 sec. ²
Copy resolution	600 dpi x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, colour mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

Printer Specifications

Print resolution	1800 dpi x 600 dpi, 1200 dpi x 1200 dpi
PDL	PCL 6 (XL 3.0), PCL 5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.6 or later Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Printer Specifications (optional)

Print controller	Embedded Fiery IC-416
Memory/HDD	2 GB / 160 GB
PDL	PostScript 3 (ver. 3019) PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.8 or later

Scanner Specifications

Scan speed	B&W / Colour: up to 160 opm with optional DF-704
Scan resolution	Max.: 600 dpi x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Colour i-Fax, IP-Fax
Resolution	Max.: 600 dpi x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to email/FTP/SMB, up to 400 job programs

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication) Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (email/FTP/SMB and fax), copy box-to-box

System Features

Security	ISO 15408 EAL IEEE 2600.1 IP filtering and port blocking SSL2, SSL3 and TLS1.0 network communication IPsec support IEEE 802.1x support FIPS 140-2 User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax receipt Print user data encryption Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts Active Directory support (user name + password + email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.
This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

² Warm-up time may vary depending on the operating environment and usage.

³ Supports x64 only.

Components and Options

AU-102 Biometric authentication	Finger vein scanner
AU-204H Magnetic stripe card reader	Requires WT-506 Working table
AU-205H Universal ID card reader	Various ID card technologies
AU-211 CA/PIV solution	Requires WT-506 Working table
DF-629 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-704 Document feeder	Dual scan automatic document feeder, capacity 100 originals
DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 and 4 support
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511 Booklet finisher	50-sheet staple finisher, 20-sheet booklet finisher, 3,300 sheets max. output
HD-524 Hard disk	Hard disk mirroring, 250 GB
IC-416 Fiery image controller	Embedded image controller for graphics-intensive applications
JS-506 Job separator	Separation for fax output, etc.
KH-102 Keyboard holder	To place USB keyboard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3 PDF enhancements	PDF/A, PDF encryption, digital signature
LK-104 v3 Voice guidance	Provides voice guidance functions
LK-105 v4 OCR text recognition	Searchable PDF
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110 v2 Enhanced image support	Generates various file formats incl. DOCX, XLSX and combines LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LU-302 Large capacity unit	8.5" x 11", 3,000 sheets / 52-256 gsm
MK-730 Mount kit	Banner paper guide
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OC-511 Original cover	Cover instead of auto document feeder
PC-110 Universal tray (x1)	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
PC-210 Universal tray (x2)	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
PC-410 Large capacity tray	8.5" x 11", 2,500 sheets, 52-256 gsm
PK-519 Punch kit for FS-533	2/3-hole punching, autoswitching
PK-520 Punch kit for FS-534	2/3-hole punching, autoswitching
RU-513 Relay unit	Required for the FS-534 and FS-534 + SD-511
SC-508 Security kit	Copy Guard function (2x required when DF-704 is installed)
SK-602 Staple kit	Added stapling functionality kit
SP-501 Stamp unit	Added fax stamp capability kit
UK-211	2 GB memory expansion, required for most i-Options, registered overlay, and concurrent use of web browser and certain other functions, including stamp print, watermark, date/time print, header/footer, image overlay and management number
UK-212 Wireless LAN	Wireless LAN to network connector
VI-508 Interface kit for IC-416	Fiery controller interface card
WT-506 Working table	Authentication device placement



KONICA MINOLTA

© 2016 KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, Count on Konica Minolta, bizhub, PageScope, and Giving Shape to Ideas are registered trademarks or trademarks of KONICA MINOLTA, INC. Trademarks of the Canadian Breast Cancer Foundation, used under licence. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design and specifications are subject to change without notice.



www.konicaminolta.ca



Item #: C258SS
01/16 - P